

Air Needle Scaler Model SP1485 (JEX-24)



AB01003

Specifications	
Impact Per Min. (bpm)	4000
No. of Needle (Chisel Width)	Ø 3 x 180 x 23pcs
Needle Option (Chisel Width Option)	Ø 2 x 180 x 53pcs
Air Inlet (PT)	3/8"
Air Pressure (Bar)	6.2
Air Consumption (L/min)	285
Mass (weight)	2.8 kg
Overall Length	335 mm
Piston (Ø X stroke mm)	24 x 22 x 56

Air Needle Scaler Model SP1480 (JEX-28)



AB00908

Specifications	
Impact Per Min. (bpm)	3800
No. of Needle (Chisel Width)	Ø 3 x 180 x 28pcs
Needle Option (Chisel Width Option)	Ø 4 x 180 x 14pcs
Mass (weight)	3.0kg (7.9lbs)
Overall Length	350mm (14.2")
Air Inlet (PT)	3/8"

Air Needle Scaler Model SP1490



AB00909

Specifications	
Impact Per Min. (bpm)	2500
No. of Needle (Chisel Width)	Ø 3 x 180 x 49pcs
Needle Option (Chisel Width Option)	Ø 4 x 180 x 35pcs
Mass (weight)	6kg (13.2lbs)
Overall Length	460mm
Air Inlet (PT)	1/4"
Piston (Ø X stroke mm)	33 x 28.5 x 94

Air Needle Scaler Model SP1495



AB01004

Specifications	
Impact Per Min. (bpm)	3800
No. of Needle (Chisel Width)	Ø 3 x 180 x 19pcs
Needle Option (Chisel Width Option)	Ø 2 x 180 x 29pcs
Air Inlet (PT)	1/4"
Air Pressure (Bar)	6.2
Air Consumption (L/min)	285
Mass (weight)	2.7 kg
Overall Length	330 mm
Piston (Ø X stroke mm)	23.5 x 20 x 73

Electric Needle Scaler Model EJC-32A



AB00204

Specifications	
Power Supply	AC115V or AC230 V, 50/60 Hz
Rated Power Consumption	300W
Rated Current	2.8A or 1.4 A
Rated Duty	30 minutes
Stroke Speed	3000 min ⁻¹
Needles to be used	Dia. 3mm x 180mm long (15pcs) or 2mm x 180mm long (32pcs)
Power Cord Length	2.5 meters
Dimensions	520mm(L) x 82mm(W) x 171.5mm(H)
Mass (weight)	4.5kg
Standard Accessories Needles	3mm(D) x 180(L), 15 pcs. mounted, extra 15pcs. incarton. Hex spanner 6 mm.

Optional Needles

Specifications	
Size	Qty per container
2mm dia x 180	100 AB00205
3mm dia x 180	100 AB00206
4mm dia x 180	50 AB00207



AB00205
AB00206
AB00207

Mini Beveler Ring Type Model AMB-0307 AB00208 Lever Type Model AMBL-0307 AB00209 HAND BEVELER



AB00208
AB00209

Specifications	
Rated air pressure	0.59 M Pa (6 kgf/cm ² , 5.9 bar)
Rated air consumption	0.9 m ³ /min
Free speed Chamfering Capacity	13,000 r.p.m. 0~3C stainless steel 0~7C mild steel (upto 4C for 1st cut)
Chamfering Angle	15° - 45°
Mass (weight)	2.9 kg

Mini Beveler Model MB-03A (Electric)



AB00210

Specifications	
Rated voltage	AC230V 50/60Hz AC110V 50/60Hz
Rated current	2A 4.5A
Rated output	430W
Chamfering Capacity	0-3C
Chamfer angle	45°
Chamfering Radius Capacity	2R 3R
Rated revolution	7100 r.p.m.
Overall length	316 mm
Mass (weight)	2.5 kg