

## **UNI 5000N Magnetic Drill**

Core Drill Dia 50mm Twist Drill Dia 16mm Rated Voltage 110/220V Rated Frequency 50-60Hz 1700W Rated Input Power 280/510rpm No-load Speed Max Attraction 16500N **Cutting Depth** 45 - 75mm 230mm Stroke 14.8/17.8Kg Net/Gross Weight

Standard Accessories Allen Wrench, Coolant Tank, Feeding Handle, Safety Belt, User Manual



AC 01026N - 110V AC01027N - 220V


## **UNI 7500 Magnetic Drill**

Cutter 75mm Cutting Shank 19mm Twist Drill Capacity 32mm Taps 25mm Morse Taper No.3 2,250kg Clamping Force

Size 630mm x 280mm x 470mm

27.7kg Weight

Standard Accessories 1 Hex. Wrench: 2.5mm, 1 Wrench 8mm, 3 Crank Handles, 1 Guard, 1 Safety Chain



AC 01029 AC 01030

## **UNI 1000 Magnetic Drill**

Core Drill Dia 100mm Twist Drill Dia 28mm Tapping Dia M26 110/220V Rated Voltage Rated Frequency 50-60Hz Rated Input Power 2380W

100-130/300/620rpm No-load Speed Max Attraction 17600N

Cutting Depth 70 - 110mm

(For cutter length beyond 75mm, a separate core cutter holder is required)

330mm Stroke Net/Gross Weight 27/32Kg

Standard Accessories Feeding Handle, Safety Belt, User Manual

Allen Wrench, Coolant Tank, Core Cutter Holder,

# **UNI 3530 Low Profile Magnetic Drill**

Core Drill Dia 38mm Rated Voltage 110/220V Rated Frequency 50-60Hz Rated Input Power 1650W No-load Speed 570rpm Max Attraction 14500N **Cutting Depth** 35mm Stroke 45mm Weight 8.5/13Kg

Standard Accessories Allen Wrench, Coolant Tank, Ratchet Wrench, Safety Belt, User Manual



AC 01224 - 110V AC01225 - 220V

## **UNI 5550 Low Profile Magnetic Drill**

Core Drill Dia 55mm Rated Voltage 110/220V Rated Frequency 50-60Hz 1900W Rated Input Power No-load Speed 550rpm Max Attraction 15500N **Cutting Depth** 50mm Stroke 60mm Weight

9/13.5Kg

Standard Accessories Allen Wrench, Coolant Tank, Ratchet Wrench, Safety Belt, User Manual



AC 01040 - 220V AC01041 - 110V

AC 01042 - 220V AC01043 - 110V

# **UNI 5550CS Low Profile V-Magnet Magnetic Drill**

Core Drill Dia 55mm Rated Voltage 110/220V Rated Frequency 50-60Hz Rated Input Power 1900W No-load Speed 550rpm Max Attraction 15500N **Cutting Depth** 50mm Stroke 60mm Weight 8.5/14.0Kg

Standard Accessories Allen Wrench, Coolant Tank, Ratchet Wrench, User Manual



AC 01037 - 220V





Min. Pipe Capacity: 3 inches

## UNI 5000CS V-Magnet Magnetic Drill

Core Drill Dia 50mm Twist Drill Dia 13mm Rated Voltage 220V 50-60Hz Rated Frequency 1700W Rated Input Power 280/510rpm No-load Speed Max Attraction 16500N 40-50mm Cutting Depth 230mm Stroke 11.7/18.2Kg Net/Gross Weight

Standard Accessories Allen Wrench, Coolant Tank, Feeding Handle User Manual







Min. Pipe Capacity: 3 inches

UNICUT

# **ALLINTON ENGINEERING & TRADING PTE LTD**

331 Jalan Besar Singapore 208983 T65 6296 0679 w allinton.com.sg E sales@allinton.com.sg

34