Power Tools




Radial Drilling Machine Z3050

Specifications

Stock Code		AC01216
Model		Z3050 x16
Max. drilling diameter (with tensile strength of 65kg/mm² in steel)		50mm
Distance from axis of spindle to column surface	Maximum	1600mm
	Minimum	350mm
Distance from spindle nose to base plate	Maximum	1210mm
	Minimum	310mm
Max. travel of arm on column		600mm
Max. travel of spindle head on arm (manual)		1250mm

Taper hole in spindle	Morse No. 5
Max. travel of spindle	315mm
Number of spindle speeds (one of which is O)	16
Range of spindle speeds (clockwise)	25-2000r/min
Number of feeds (one of which is O)	16
Range of feeds	0.04-3.2mm/r
Main drive motor power	4kW
Weight of the machine (approx)	3500kg
Machine overall dimensions (L x W x H)	2490 x 1060 x 2625mm



QC12Y Hydraulic Pendulum Shearing Machines

- The machine employs hydraulically-driven swing beam, the steel plate welded structure and accumulator-based pullback cylinder with steady and reliable operation.
 Indicator-based adjustment of gap of blade is convenient and fast.
 The machine is equipped with lighting alignment device, and uses stepless control for the stroke of up tool carrier.
 The machine uses protection fence for safe operation.
 Digital display device for size of back gauge and shearing times available.

AC01217



Shear Size (T x W) (mm) Shear Angle Strokes Backgauge Range Main Motor (min¹) (mm) (kW) Stock Code Model QC12Y -16 x 4000 AC01217 16 x 4000 2°20 18.5 15 300 4745 x 2477 x 2035 > 5 20-800 AC01218 30 000 5900 x 3000 x 3300 20 x 5000 2°30′ ≥ 4 20-800 37 AC01219 25 x 3200 26 000 4200 x 2400 x 2500 40-1000

Hack Sawing Machine

AC00980	AC00981
HR 14	HR 16
6-1/2 " x 6-1/2 "	8-1/2 " x 8-1/2 "
14" x 1" x 50"	16" x 1" x 50"
6-1/4" - 3-1/2"	6-1/4" - 3-1/2"
61 rpm - 81 rpm	61 rpm - 81 rpm
1/3 - 1/2 220V	1/3 - 1/2 220V
36" x 15"	36" x 15"
25"	27"
115kg	125kg
2 litre	2 litre
	HR 14 6-1/2 " x 6-1/2 " 14" x 1" x 50" 6-1/4" - 3-1/2" 61 rpm - 81 rpm 1/3 - 1/2 220V 36" x 15" 25"

HR 14 AC00980 HR 16 AC00981



Electric Bandsaw Machine

Stock Code	AC00982	AC00983
Model	RF-712	RF-916
Capacity-Vise	7" Round	9" Round
	7" x 12" Rectangle	9" x 16" Rectangle
Blade Speed	86-130-180-235 FPM 60Hz	50-125-200-275 FPM 60Hz
	70-110-150-196 FPM 50Hz	40-105-165-230 FPM 50Hz
Motor	1 Hp 4 pole 60Hz 1725rpm	1-1/2 Hp 4 pole 60Hz 1725rpm
	1 Hp 4 pole 50Hz 1420rpm	1-1/2 Hp 4 pole 50Hz 1420rpm
Blade Size	3/4" x 0.032" x 93"	1" x 0.037" x 117"
Machine Dimensions	L 49" x W 17" x H39.5	L 63" x W 30.7" x H41.3
	L 49" x W 17" x H63.5	L 63" x W 30.7" x H41.3
Weight	N.W. 125kgs (275lbs)	N.W. 285kgs (625lbs)
	G.W. 150kgs (330lbs)	G.W. 320kgs (704lbs)
Packing	50.5 " x 18" x 39" (20.5Cuft)	62" x 32" x 45" (51.7Cuft)



RF 712 AC00982 RF 916 AC00983

AET

ALLINTON ENGINEERING & TRADING PTE LTD

331 Jalan Besar Singapore 208983 **T65** 6296 0679 **W** allinton.com.sg **E** sales@allinton.com.sg