


Mitter Saw for Aluminium & Wood Cutting Professional Portable Saw 250 JET



AC00809

Specification

- Tilting saw unit on the vertical axis up to 45° on the left hand side
- Induction motor with brake system
- Every angle locking knob
- Middle vertical handle
- Rettified working tables
- Possibility of clamps on both sides
- Technical Data:
 - Power consumption: 1200 Watt
 - Die-cast aluminum
 - Max Cut: 145mm x -Y= 45 (Width x Length)
 - Max Cutting Angle 90mm x -Y=45(45° x 45°)
 - Max Cutting Oblique: X=145mm-Y=40(45°)
 - Max Block Size: 580x580x500 mm
 - Blade: 250mm -30mm Z40
 - Number Revolutions per Minute: 2800
 - Work plan sizes: 430x300x38mm
 - Cod. 250 JET-01- EAN 8032770664733
 - Weight 20 Kg

Professional Portable Saw 300 JE



AC00810

Specification

- Noiseless induction motor with brake system
- Safety motor cover
- Tilting saw unit on the vertical axis up to 45° on the left hand side
- Possibility of clamps on both know
- Every angle locking knob
- Bronze insert in the angle locking group
- Exclusive double sliding square
- Technical Data:
 - Power consumption: 1400 Watt
 - Max Cut: 140mm X=-Y=70 (Width x Length)
 - Max Cutting Angle: 95mm x X= -Y=70 (45° x 45°)
 - Max Cutting Oblique: X =140 mm -Y =45(45°)
 - Max Vertical Cut Straight: mm x =12 -Y = 95
 - Max Block Size: 580 x 580 x500 mm
 - Blade: 300 mm -30 mm Z 72
 - Number Revolutions for Minute: 2980
 - Work plan sizes: 400 x285x50 mm
 - Cod.300 JE m WZ72-EAN 8032770660070
 - Weight 19 kg

Radial Arm Saw JUNIOR 640



AC01695

Radial Arm Saw BEST 960



AC01697

Stock Code	AC01694	AC01695	AC01696	AC01697
Model	PROFESSIONAL 400	JUNIOR 640	BIG 800	BEST 960
Three phase Motor Power	2HP 1.5kW	4 HP 3 kW	4 HP 3kW	4HP 3kW
Angle phase Motor Power	1.5 HP 0.9kW	3 HP 2.2kW	3HP 2.2kW	3HP 2.2kW
Motor Speed	2800 r.p.m	2800 r.p.m	2800 r.p.m	2800 r.p.m
Blade Diameter	Ø300 mm	Ø350mm	Ø350mm	Ø350mm / 400mm
Blade Bore Diameter	Ø20mm	Ø30mm	Ø30mm	Ø30mm
Shaft dimension	Ø 16 x 80mm	Ø 25 x 80mm	Ø 25 x 80mm	Ø25 x 80mm
Dust chute diameter on blade guard	Ø 60mm	Ø 60mm	Ø 60mm	Ø 60mm
Rear dustchute diameter	Ø100mm	Ø100mm	Ø100mm	Ø100mm
Table diameter	560x800mm	975x 1580mm	1145x1860mm	1200x2000mm
Max cut width Ø350	15x 380mm (Ø300)	20x550mm	20x 710mm	20 x 870mm
Width of cut h max Ø400	-	-	-	20 x 865mm
Maximum cut depth Ø350	75 x 320mm (Ø300)	100x 480mm	100x 640mm	100x800mm
Max. height of cut Ø400	-	-	-	125 x 770mm
Max. cut dept Ø350	75mm (Ø300)	100mm	100mm	100mm
Max. cut dept Ø400	-	-	-	125mm
Max. height of blade from table Ø350	60mm (Ø300)	70mm	70mm	110mm
Max. height of blade from table Ø400	-	-	-	85mm
Max. cutting height at 45° Ø350max	45mm (300)	60mm	60mm	60mm
Max. cutting height at 45° Ø400 max	-	-	-	80mm
Max. cutting height arm 45° on left side	15 x260>75 x 225mm	20x 380>100x450mm	20x500.100x450mm	20x 615> 100 x565mm
Max. cutting height arm 45° on right side	15 x 70>75x35mm	20x 190.100x140mm	20x310>100x260mm	20x 425> 100x375mm
Gross Weight	80 kg	180	198kg	269 kg