

### No. 418 Oiler


- Hand-operated, pumps easily by thumb action
- Completely portable, large pan catches oil run-off, chips
- Oil is double-filtered and recirculated through reservoir
- Chip pan 14½ / 2" (362mm) dia., 8½" (212mm) deep, hose length 54" (1,4m).

Stock Code	Model No.	Description
AH10883	418	Oiler with 1 Gallon (3,78 Ltrs) of Thread Cutting Oil
AH72342	402	Utility Oiler (Consists of Pump, Hose, and Attachments to screw onto 1-Gallon Oil Can (Oil Can and Oil not included)

AH10883



AH72342



### Ridgid Electrical Cut, Crimp and Punch Kit.

#### ELECTRICAL TOOLS RE 60 ELECTRICAL TOOL

##### Specifications

- 60 kN hydraulic force output to cut armored cable up to 50 mm O.D., crimp Cu/Alu lugs up to 300 mm<sup>2</sup> and punch round holes up to 4" (116mm)
- Automatic ram retraction when cutting and crimping
- Rubber overmolded grips for superior comfort and control
- Bright white LED workspace illumination light
- On/Off button for disabling tool when changing heads or transporting
- Nylon straps for greater tool security
- Approximate Cycle Time: 5 seconds
- Service Interval: 32,000 cycles

##### Ordering Information

#### KITS\*

STOCK CODE	DESCRIPTION	NO. OF HEADS	CUT SC-60C	CRIMP LR-60B	PUNCH PH-60B
AH47228	RE 60 Cut, Crimp and Punch Kit**	3	✓	✓	✓
AH47223	RE 60 Cut & Crimp Kit**	2	✓	✓	-
AH47208	RE 60 Crimp Only Kit	-	-	✓	-
AH47213	RE 60 Cut Only Kit (Cu/Al Blades)	1	✓	-	-
AH47218	RE 60 Punch Only Kit	-	-	-	✓

#### ACCESSORIES

STOCK CODE	DESCRIPTION	WEIGHT	
		(lb.)	(kg)
AH47768	RE 60 Electrical Tool Only	5.5	2.5
AH47753	LR-60B Latching Round Crimp Head Only	3.3	1.5
AH47763	PH-60B Knockout Punch Head Only	3.5	1.6
AH47918	SC-60C Scissor Cutter Head w/ Blade for Cu/Alu Cable	4.7	2.1
AH49408	SC-60C Scissor Cutter Head with ACSR Blades	4.7	2.1
AH47773	RE 60 Electrical Tool Case Only	10.1	4.6
AH43323	18V Advanced Lithium 2.0Ah Battery	1.0	0.5
AH43328	18V Advanced Lithium 4.0Ah Battery	1.5	0.7
AH43333	Advanced Lithium Battery Charger	1.8	0.8

\*\* All Kits Include: RE 60 Electrical Tool, (2) 18V Advanced Lithium 2 batteries, battery charger and blow-molded case.

\* Includes SC-60C Cutter Head with Copper/Aluminum Blades.



AH47228



AH49303

AH53543

### RIDGID B-500 TRANSPOTABLE BEVELLER

##### Specifications

- Capacity: 3½" (100 mm) pipe and larger, flat plate; steel & stainless steel
- Pipe Wall/ Plate Thickness: min 0.188" (4,8 mm) / max 0.5" (12,7 mm)
- Bevel Angles: 37.5° (standard, included), 30° & 45° (optional cutter heads)
- Cutter Head: rated for most steel & stainless steel\*
- Land Width: 0.3/16" (4,8 mm) in approximately 1/32" (0,8 mm) increments
- Motor Type: 230 V / 115 V, 50 / 60 Hz, universal
- Operating Speed: 950 RPM (no load)
- Weight: 24 kg
- Size: 40,1 × 29,2 × 33,8 cm (L × W × H)
- Standard Kit: beveller, manual crank handle, 37,5° cutter head, 6-4 edged inserts, torque driver, screws

\* Application, material, pipe diameter, wall thickness, pipe coatings, operator function, etc. are all key factors that will determine insert life. Beveller cutting head and inserts are optimized for standard A53 mild steel pipe; reduced insert life can be expected on other materials.

##### Ordering Information

STOCK CODE	DESCRIPTION	WEIGHT (kg)
AH49303	Portable Pipe Beveller w/37,5° Cutter Head (230 V, CE)	24
AH53543	Portable Pipe Beveller w/37,5° Cutter Head (115 V, CE)	24
AH48863	37,5° Cutter Head w/6 Inserts, 1 Anti-Seize Grease, 8 Screws	1,1
AH48858	30° Cutter Head w/6 Inserts, 1 Anti-Seize Grease, 8 Screws	1,1
AH48868	45° Cutter Head w/6 Inserts, 1 Anti-Seize Grease, 8 Screws	1,1
AH48873	Pack of 6 Inserts, 1 Anti-Seize Grease, 2 Screws, Case	0,1
AH48883	Anti-Seize Grease - 1 Tube	0,1
AH48888	Torx Wrench T15/S7	0,1
AH48893	Spanner Wrench	0,1
AH48898	3/16 Hex Wrench	0,1

49303 & 53543 kits contain: beveller (230 V / 115 V), manual crank handle, 37,5° cutter head, 6 - 4 edged inserts, torque driver, screws

ALLINTON ENGINEERING & TRADING PTE LTD

331 Jalan Besar Singapore 208983

T65 6296 0679 W allinton.com.sg E sales@allinton.com.sg