


Self-Charge Grouting Gun



Volume chargeable approx. 1 litre.
Net Weight: 875g
(Empty)

- * Handy-Remarkable High Efficiency.
- * No Power Required- Unbelievable down cost.
- * Perfect Pressure Grouting by two special piston packings.
- * Minimum falling loss of material.
- * Simple Mechanism
- * Quick turn Guide for easy cleaning.



Hand Injector Grout Pump



Model: T-SDA-27
Drive: Diaphragm manual operation
Speed Control: Stroke control Output (cc/stroke): 115-130
Max. Output Pressure (kgf/cm²): 3
Conveying Distance: Horizontal 5m or Vertical 5m
Hopper Capacity (litre): 10
Dimension (mm): 295W x 740L x 650H
Weight (kg): 27

Foot Injector Grout Pump



Model: TM-5
Drive: Foot plunger
Speed Control: Stroke control
Output (cc/stroke): 10
Max. Output Pressure (kgf/cm²): 25
Conveying Distance: Horizontal 3m or Vertical 3m
Hopper Capacity (litre): 3
Dimension (mm): 280W x 470L x 600H
Weight (kg): 7

New Type Foot Injector Grout Pump



Model: TM-50
Drive: Foot plunger
Speed Control: Stroke control
Output (cc/stroke): 10 - 50
Max. Output Pressure (kgf/cm²): 45
Conveying Distance: Horizontal 3m or Vertical 3m
Hopper Capacity (litre): 8
Dimension (mm): 410W x 500L x 700H
Weight (kg): 16.7

Mini Pump



Model: TS-002
Power: 0.2kW, 100V Single Phase
Speed Control: 50Hz, 27A/60Hz, 32.5A
Output (litre/min): 2.0 - 2.5
Max. Output Pressure: 1.4 Mpa (14kgf/cm²)
Conveying Distance: Horizontal 3m or Vertical 3m
Hopper Capacity (litre): 7
Pumping Tube: Dia. 17 1500 Three Rollers
Dimension (mm): 230W x 440L x 550H
Weight (kg): 28

Slurry Pump



Model: TS-SP
Power: 0.75kW, 100V Single Phase
Speed Control: Pulley
Output (litre/min): 13.7
Max. Output Pressure: 1.4 Mpa (14kgf/cm²)
Conveying Distance: Horizontal 20m or Vertical 10m
Hopper Capacity (litre): 35
Pumping Tube: Dia. 32 11100 Two Rollers
Dimension (mm): 530W x 1000L x 600H
Weight (kg): 75