

# Construction Tools

## Air Vibrator c/w 2 Mtr Hose

Range VP Optionals

- Vibrators from 32 to 55mm  $\phi$  available also with rigid rod and/or with spatulapop
- Line lubricating device
- Vibrator rubber hose longer than 2m standard can also be supplied



MODEL NO		VP-32	VP-44	VP-55	VP-75
Stock Code	Unit	AA00085	AA00086	AA00087	AA00088
Needle $\phi$	mm	30	40	50	80
Needle Length	mm	250	280	320	375
N Vibrations	1'	14.000	13.000	12.500	12.000
Amplitude	mm	0,8	1,2	1,56	2
Compacting Power	cum/h	8	15	23	28
Action $\phi$	cm	50	60	70	90
Centrifugal Force	Kg	75	225	400	700
Schleuderkraft - Intensite de vibration	KN	0,75	2,25	4	7
Operating Pressure	Atm-Atu	6	6	6	6
Air Consumption	lt/1' max	400	500	600	1600
Tube - Rubber Hose	m	2	2	2	2
Total Weight	Kg	4	5	6	13

## EXEN (JAPAN)

Handy held vibrator(External EK)



Model	Output (W)	Input (V)	Input (A)	Frequency (Hz)	Total Height (mm)	Head(dia. X length) (mm)	Weight (kg)
EKCA W/ Holder	280	100	5	160-200	404	Vibrating face 76 X 113	4.7
					407	Vibrating face 120 X 150	5.8
EKD W/ Holder	280	100	5	140-180	424	Vibrating face 110 X 150	5.9
					427	Vibrating face 200 X 200	7.6

## Electric Vibrator

Vibrator with Rigid rod and electric motor, single-phase

- Input 220-230V -50-60 Hz
- Double insulation
- IP 23
- Needle with rod length 865mm
- Needle  $\phi$  22mm (also VR 25 E version with 23 $\phi$  x 556mm)
- Cordset with plug ca 4m
- Motor and needle total weight 4.9kg



## Single Phase Models

Square Head Flexible Shaft Vibrator c/w Motor




Stock Code	Size
AA00079	35mm x 4 m
AA00080	35mm x 6 m
AA00081	45mm x 4 m
AA00082	45mm x 6 m
AA00083	50mm x 4 m
AA00084	50mm x 6 m

## Motor & Head Assembly



## Portable Electric Models



Wide Selection of Heads and Flexible Shafts