

Garden & Carpentry Tools

Rockwool

Product Description

Rockwool is a lightweight mineral fiber product designed for economic and effective insulation on thermal, acoustical and fire protection of building, industrial and marine industry. It consists of long, fine fibre spun from molten natural rock bonded with thermosetting resin.

Benefits & Features

- Low Thermal Conductivity (0.034 W/mk)
- Wide Range of Operating Temperature (-100 °C to 820 °C)
- Non-Combustible
- Superior Acoustical Properties
- Excellent Corrosion and Moisture Resistance
- Asbestos-Free

Brands Available

FOSTER®, LAPINUS, KEUMKANG, BRADFORD.

Other Fabricated Products

Elbows, Valves, Flanges and Tees.



Rigid Slab

AI00565



Wiremesh Blanket
Flexible Blanket



AI00566
AI00567



Pipe Sectional

AI00568

Product Range

Rigid Slab

Density	(kg/m ³)	40-200
Length	(mm)	1200
Width	(mm)	600
Thickness	(mm)	25-100

Wiremesh Blanket

Density	(kg/m ³)	60-128
Length	(mm)	2000-5000
Width	(mm)	900 & 1200
Thickness	(mm)	25-100

Flexible Blanket

Density	(kg/m ³)	40-100
Length	(mm)	1000-1200
Width	(mm)	15-800
Thickness	(mm)	25-100

Pipe Sectional

Density	(kg/m ³)	110-180
Length	(mm)	1000-1200
Width	(mm)	15-800
Thickness	(mm)	25-100

Fibreglass Wool

Product Description

Fibreglass Wool is a lightweight glass fibre product, designed for economic and effective insulation of thermal, acoustic and fire protection of building, industrial, plant equipment and marine industry. It consists of long, fine glass fibre bonded with thermosetting resin.

Benefits & Features


- Low Thermal Conductivity (0.034 W/mk)
- Wide Range of Operating Temperature (-100 °C to 450 °C)
- Non-Combustible
- Excellent Corrosion and Moisture Resistance
- Extremely Lightweight
- Superior Acoustical Properties
- Asbestos-Free

Brands Available

FOSTER®, ACI, KEUMKANG, BRADFORD, KIMMCO, POLYGLASS.

Other Fabricated Products

Elbows, Flanges, Tees & Laminated Products



Semi-Rigid / Rigid Board

AI00569



Flexible Blanket

AI00570



Pipe Sectional

AI00571

Product Range

Board

Density	(kg/m ³)	32-80
Length	(mm)	2300-2440
Width	(mm)	1200
Thickness	(mm)	25-100

Flexible Blanket

Density	(kg/m ³)	10-48
Length	(mm)	10,000-30,000
Width	(mm)	1200
Thickness	(mm)	25-100

Pipe Sectional

Density	(kg/m ³)	64-80
Length	(mm)	1000-1200
Width	(mm)	15-600
Thickness	(mm)	25-100