

Garden & Carpentry Tools

Welded Mesh

SHEETS Standard Specifications

BRC Ref No.	BS 4483 or SS:32 Ref No.	Main Wire		Cross Wire		Cross-Sectional Area		Mass Per Unit Area kg/m ²
		Size mm	Spacing mm	Size mm	Spacing mm	Main mm ² /m	Cross mm ² /m	
SQUARE MESHES								
A10	A393	10	200	10	200	393	393	6.16
A9	-	9	200	9	200	318	318	4.99
A8	A252	8	200	8	200	252	252	3.95
A7	A193	7	200	7	200	193	193	3.02
A6	A142	6	200	6	200	142	142	2.22
D12	-	12	100	12	100	1131	1131	17.78
D11	-	11	100	11	100	950	950	14.91
D10	-	10	100	10	100	785	785	12.32
D9	-	9	100	9	100	636	636	9.98
D8	-	8	100	8	100	503	503	7.90
D7	-	7	100	7	100	385	385	6.04
D6	-	6	100	6	100	283	283	4.44

ROLLS Standard Specifications

BRC Ref No.	BS 4483 or SS:32 Ref No.	Main Wire		Cross Wire		Cross-Sectional Area		Mass Per Unit Area kg/m ²
		Size mm	Spacing mm	Size mm	Spacing mm	Main mm ² /m	Cross mm ² /m	
SQUARE MESHES								
A6	A142	6	200	6	200	142	142	2.22
A5	A98	5	200	5	200	98	98	1.54

BRC Ref No.	BS 4483 or SS:32 Ref No.	Main Wire		Cross Wire		Cross-Sectional Area		Mass Per Unit Area kg/m ²
		Size mm	Spacing mm	Size mm	Spacing mm	Main mm ² /m	Cross mm ² /m	
RECTANGULAR MESHES								
B13	-	13	100	10	200	1328	393	13.50
B12	1131	12	100	8	200	1131	252	10.9
B11	-	11	100	8	200	950	252	9.43
B10	785	10	100	8	200	785	252	8.14
B9	-	9	100	8	200	636	252	6.97
B8	503	8	100	8	200	503	252	5.93
B7	385	7	100	7	200	385	193	4.53
B6	283	6	100	7	200	283	193	3.73
B5	196	5	100	7	200	196	193	3.05
C12	-	12	100	8	400	1131	126	9.87
C11	-	11	100	8	400	950	126	8.44
C10	785	10	100	6	400	785	71	6.72
C9	636	9	100	6	400	636	71	5.55
C8	503	8	100	5	400	503	49	4.34
C7	385	7	100	5	400	385	49	3.41
C6	283	6	100	5	400	283	49	2.61

Building Products

Angle Bead

Protects plaster arrises; one size adjusts for thickness, ref 550 standard, ref 558 Maxicon (economy version). Also available in stainless steel.



AI00904
50 LGTH x 2700mm / box


Form Rib



AI00504
AI00505

Rib-lath

Used for external rendering and for interior plastering where high corrosion resistance is needed; ref 267.



L.D. AI00505
H.D. AI00504
0.30 (THK) x 2400 (L) x 610 (W)mm


Plaster Stop

Finishes plaster edges. In four depths: ref 562 10mm, ref 563 13mm, ref 566 19mm. Also available in stainless steel.



AI00906
50 LGTH x 2440mm / box

Exmet



AI00509 (2½" width)
AI00510 (4" width)
AI00511 (8" width)

Exmet



AI00506 (65mm width)
AI00507 (100mm width)
AI00508 (150mm width)

ALLINTON ENGINEERING & TRADING PTE LTD

331 Jalan Besar Singapore 208983

T65 6296 0679 W allinton.com.sg E sales@allinton.com.sg