




- -70Mpa max working pressure; keep the accuracy $\pm 3\%$. -5 models with the range from 232-44593N.m
- -360*180 degree swivel &360*360 degree swivel allow the wrench free to operation with no space limitation.
- -More accuracy and easier when the wrench direct operate on the nuts.
- -Compact design with longer arm fully advances the reliability.
- -Compact design with the raw material of advanced -aluminum-titanium alloy, high intense.
- -The new locking coupler ensures the oil keep free access.









LOW series is the professional Low profile hydraulic torque wrench which KANAZAWA vigorously extends in international market. Compare with the square drive hydraulic torque wrench, this series work directly on the nuts, and its body suits well in the narrow space. LOW covers the nuts from \$19 to \$175.To fulfill all different working situations, the user can just replace the ratchet link because the ratchet link is changeable, or add the reducer. KANAZAWA provide after-sales service all over the world, and already got the approved by TUV certificate.

LOW Series Selection Chart

Stock Code	Model	Torque (N.m)	Nut Size (mm)	Power Head	Work Head	Size (mm)				
				Weight (Kg)	Weight (Kg)	L	H1	H2	W1	W2
AQ04652	2LOW	232~2328	19~55	1	1.6	196.4	125.9	102.3	32	51
		241~2414	60	1	1.7	196.4	128.5	105	32	51
AQ04653	4LOW	585~5858	34~65	2	4.4	245	177	135.7	42	66
		647~6474	70~80	2	4.6	246	187	145.7	42	66
AQ04654	8LOW	1094~10941	41~95	3.3	8	300	207	169	53	83
		1177~11774	100~105	3.3	8.4	301	216	178	53	83
AQ04655	14LOW	1852~18521	20~117	5.5	11.6	361	239	204	64	99
AQ04656	30LOW	4188~41882	110~155	11.4	29	430	303	272	85	131
		4459~44593	160~175	11.4	30	441	315	285	85	131

KANAZAWA