Hydraulic



CLP series

Single-Acting Pancake Lock Nut Cylinder





Capacity:60 ~520Ton Stroke:45~50mm Maximum Operating Pressure: 700bar



CLP Series Selection Chart

Stock Code	Model	Capacity	Stroke	Min Height	Outside Diameter	Euective Area	Oil Capacity	Saddle	Weight
		(Ton)	(mm)	(mm)	(mm)	(cm ²)	(cm³)	Diameter (mm)	(Kg)
AQ04895-K	CLP602	60	50	125	140	86.6	432	104	15
AQ04896-K	CLP1002	100	50	137	175	146.8	734	136	26
AQ04897-K	CLP1602	160	45	148	220	231.3	1040	171	44
AQ04898-K	CLP2002	200	45	155	245	285.6	1285	190	57
AQ04899-K	CLP2502	260	45	159	275	366.8	1650	216	74
AQ04900-K	CLP4002	400	45	178	350	559.5	2517	266	134
AQ04901-K	CLP5002	520	45	192	400	730.6	3287	305	189

MP-Series Electric Pumps

* Double-speed designed, infinitely variable pressure adjustment between 0-700bar.

* Modularity product, supply more than 200 kinds electric pump, and there have 5 different valves can choose, 4-56L multiple oil tank, and many different electrical machinery (100-120V, 200-240V, 350-420V).

* MP-series electric hydraulic pumps suits to a wide variety of industrial and application fields to work as lifting, pushing, pulling bending, pressing, punching and many other applications. It is economical and durable power source.

Stock Code	AQ04887		
Model	MP08HT13		
Source of Power	230V/50hz		
Power	1.0KW single phase power		
Flow L/min	low 5,5		
Flow L/min	high 0,6		
Valve tape	TypeH: Solenoid Valve(double-acting) input/lock/output		
Volume	10L/8L		
Weight (Kg)	21.5		

Hydraulic Hoses for Jack

Stock Code	Model	Model & p	Max operating	Hose end		Hose length	
		woder & p	Pressure (Mpa)	end one	end two	(m)	
AQ04657	JH7818	JH78 Series hydraulic house		72	3/8"NPT	3/8"NPT -	1.8
AQ04658	JH7845						4.5



Type H: Solenoid Valve(double-acting)

KANAZAWA

ALLINTON ENGINEERING & TRADING PTE LTD 326 331 Jalan Besar Singapore 208983 T65 6296 0679 W allinton.com.sg E sales@allinton.com.sg

Allinton Catalogue 2017 15.08.2017.indd 326