









G series

Glycerin Filled Hydraulic Pressure Gauge

- ▲ Standard calibration with dual scale reading for psi and bar.
- ▲ All the pressure sensing components are sealed with glycerin and dampened proof to guarantee durability.
- ▲ Including a safety seal ring and pressure equaling membrane.

Stock Code	Model & Picture		Port	Face Diameter (mm) & Pressure Range (Mpa)	Gauge Adaptor
AQ04669	GN0607-S		1/4 NPT External screw thread	MPa/Bar Double Scale 0-70 MPa (Digital Display)	
AQ04670	GG1010		1/2 BSP External screw thread	MPa/Bar Double scale 0-100MPa	

Super High-Pressure Series Hydraulic Component (in common use)

Stock Code	Model & Picture		Description	Application	Hydraulic Symbol
AQ04671	V-66 Manually Operated Check Valve		Used for load holding applications with single and double acting cylinders. Valve is manually opened to allow oil to flow back to tank when cylinder retracts.	Single-acting hydraulic pump & Double-acting hydraulic pump	
AQ04672	V-82 Needle Valve		The control cylinder speed can also be used as shut-off valve for temporary load holding. 3/8NPT Female ports.	Single-acting hydraulic pump & Double-acting hydraulic pump	

ALLINTON ENGINEERING & TRADING PTE LTD
 331 Jalan Besar Singapore 208983
 T65 6296 0679 W allinton.com.sg E sales@allinton.com.sg

KANAZAWA