

HAND CHAIN HOISTS VH5 VL5 VP5

'VH' Series

With a High-hardened special alloy steel load chain, and equipped With a thrust bearing on the bottom hook (only for the capacity up to 10 tones)


'VL5'-'VP5' Series

With a hardened special alloy steel load chain



Stock code	AQ00001	AQ00003	AQ00005	AQ00007	AQ00009	AQ00011	AQ00013	AQ00014	AQ00028	AQ00015
Capacity(t)	1/2	1	2	3~5	7 1/2~10	15~20	15~20	15~20	15~20	15~20
Model number	VH5-05	VP5-05 VL5-05	VH5-10 VL5-10	VH5-15 VL5-15	VH5-20 VL5-20	VH5-30 VL5-30	VH5-50 VL5-50	VH5-75 VL5-75	VH5-90 VL5-90	VH5-92 VL5-93
Standard Lift(m)	2.5	2.5	2.5	2.5	3.0	3.0	3.0	3.5	3.5	3.5
Net Weight(kg)	8.6	8.3	11.5	11.3	13.8	13.5	21.6	21.0	23.0	22.0
Head Room(mm)	305	285	345	315	370	340	425	380	505	475
Pull to Lift Load	(kg) 25 (N) 245	(kg) 25 (N) 245	(kg) 33 (N) 324	(kg) 33 (N) 324	(kg) 34 (N) 333	(kg) 34 (N) 333	(kg) 34 (N) 333	(kg) 35 (N) 343	(kg) 35 (N) 343	(kg) 39 (N) 382
Test Load(t)	0.75	0.75	1.5	1.5	2.25	2.25	3.0	3.0	4.5	4.5

V HANGER



Suspending Head for Chain Block

If logs or iron pipes are at hand a dependable support for the chain block can be easily erected with a single spanner.

VKS-10 (Option)



TYPE	Tripod use
CODE NO.	VK-10
WORKING LOAD	1000K
LEGS	Steel pipe 48.6mm
WEIGHT	5.0kg

CHAIN HOISTS



Moving products from one place to another



Uprooting trees



Installing under-water pump



Laying conduits and pipelines