
# **Welding Products**

# WELDMASTER® Welding Cable





Main Products bare wires magnetic wires rubber insulated electric wires plastics insulated electric wires tough rubber sheathed arc welding electrode cable tough rubber sheathed flexible cables for general purposes PVC-insulated & PVC - sheathed power cable PVC-insulated & PVC - sheathed control cable PVC-insulated & PVC - sheathed signal cable

Welding Cable Black		Welding Ora		Black No Ca			Veoprene ble
Stock Code	Model	Stock Code	Model	Stock Code	Model	Stock Code	Model
AS00105M	300AMP	AS00109	300AMP	AS00113	300AMP	AS00116	300AMP
AS00106	400AMP	AS00110	400AMP	AS00114	400AMP	AS00117	400AMP
AS00107	500AMP	AS00111	500AMP	AS00115	500AMP	AS00118	500AMP
AS00108	600AMP	AS00112	600AMP	-	-	-	-

## WELDMASTER®

**Gouging Rod** 



	MA RU				
Stock Code	AS00091	AS00092	AS00093	AS00094	AS00095
Size(mm)	4.5 x 305	5.0 x 305	6.5 x 305	8.0 x 305	9.5 x 305

# ATLANTIC

Welding Rod



#### CHE40

Welding Rod for Mild Steel AWS A5.1 E6013

Stock Code	AS00660	AS00661	AS00662
Size(mm)	2.5 x 350	3.2 x 350	4.0 x 400

#### CHE43

Welding Rod for Mild Steel AWS A5.1 E6019

Stock Code	AS00663	AS00664	AS00665
Size(mm)	2.5 x 350	3.2 x 350	4.0 x 400

#### CHE56

Low Hydrogen Welding Rod for High Tensile Steel AWS A5.1 E7016

Stock Code	AS00666	AS00667	AS00668
Size(mm)	2.5 x 350	3.2 x 350	4.0 x 400

Flexible Copper - core cable for welding machines 1. Application-The product is applied up to A.C 200 V and pulsating D.C. 400V at the secondary of welding machine against the earth and connecting welding guns. The Max. continuous operating temperature of conductor is 65°C.

2. Type YH 3. Standard of Product-The product verified by CCEE accors with the demands of GB 5013.3 85 (equal to IEC 245)

4. Construction



1. conductor of the cable 2. isolated layer lapped thermo-resistant film or other fiber tapes 3. rubber insulated sheath

5. Specification

	Conductive core				
of conductor	No. of wire x Dia.	Dia. of cable	of cable	at 20°C not mo	re than rad./km
mm	mm	mm	kg/km	tinned	untinned
10	322/0.20	9.7	140	1.91	1.95
16	513/0.20	11.5	212	1.16	1.19
25	798/0.20	13.0	308	0.758	0.780
35	1121/0.20	14.5	423	0.536	0.552
50	1596/0.20	17.0	592	0.379	0.390
70	2214/0.20	19.5	828	0.268	0.276
95	2997/0.20	22.0	1088	0.198	0.204
120	1702/0.20	24.0	1374	0.161	0.164
150	2135/0.30	27.0	1666	0.1529	0.132
185	1443/0.40	29.0	2044	0.1069	0.108

### **Brazing Alloy Rod**



Stock Code	AS00641	AS00642
Size(mm)	1.5	2.5

#### **CHE581**

#### High Toughness Welding Rod for High Tensile Steel AWS A5.1 E7018-1/E7018

Stock Code	AS00669	AS00670	AS00671	AS00672
Size(mm)	2.5 x 350	3.2 x 400	4.0 x 400	5.0 x 400

#### **CHS002**

#### Welding Rod for Extra-low Carbon Stainless Steel AWS A5.4 E308L-16

Stock Code	AS00673	AS00674	AS00675
Size(mm)	2.5 x 300	3.2 x 350	4.0 x 350

#### **CHS022**

Welding Rod for Extra-low Carbon Stainless Steel AWS A5.4 E316L-16

Stock Code	AS00676	AS00677	AS00678
Size(mm)	2.5 x 300	3.2 x 350	4.0 x 350

#### **CHS062**

Welding Rod for Stainless Steel AWS A5.4 E309L-16

Stock Code	AS00679	AS00680	AS00681
Size(mm)	2.5 x 300	3.2 x 350	4.0 x 350

331 Jalan Besar Singapore 208983 T65 6296 0679 W allinton.com.sg E sales@allinton.com.sg