

Welding Products

Dark Glass

2" x 4"

AS00228 No 10
AS00342 No 11
AS00343 No 12
AS00344 No 13



Clear Glass 2"

x 4" AS00229



Nozzle Cleaner



AS00226

Nozzle Cleaner (Box Type)



AS00227

Tempilstiks

Tempilstiks are made of materials with melting points calibrated to a guaranteed tolerance of $\pm 1\%$. There are a total of 103 temperature ratings with melting points systematically spaced between 100°F/38°C and 2500°F/1371°C. Most can be certified to be lead and sulfur free. Every Tempilstik is traceable by lot number to the specific batch of raw material from which it was made.

AS00247



Tempilstik, Tempilaq and Tempil Pellets are available in the following temperatures:

°F	°C	°F	°C	°F	°C	°F	°C	°F	°C	°F	°C
100	38	206	97	325	163	575	302	1300	704	2150	1177
103	39	213	101	331	166	600	316	1350	732	2200	1204
106	41	219	104	338	170	625	329	1400	760	2250	1232
109	43	225	107	344	173	650	343	1425	774	2300	1260
113	45	231	111	350	177	700	371	1450	788	2350	1288
119	48	238	114	363	184	750	399	1480	804	2400	1316
125	52	244	118	375	191	800	427	1500	816	2450	1343
131	55	250	121	388	198	850	454	1550	843	2500	1371
138	59	256	124	400	204	900	482	1600	871		
144	62	263	128	413	212	932	500	1650	899		
150	66	269	132	425	218	950	510	1700	927		
156	69	275	135	438	226	977	525	1750	954		
163	73	282	139	450	232	1000	538	1800	982		
169	76	288	142	463	239	1022	550	1850	1010		
175	79	294	146	475	246	1050	566	1900	1038		
182	83	300	149	488	253	1100	593	1950	1066		
188	87	306	152	500	260	1150	621	2000	1093		
194	90	313	156	525	274	1200	649	2050	1121		
200	93	319	159	550	288	1250	677	2100	1149		

* Series "R" tempil Pellets available in these temperatures, 550°F and below. Regular Pellets can be used for reducing atmosphere. Aerosol Tempilaq not available below 150°F/66°C.

Cable Lux

Stock Code	Size
AS00214	300AMP
AS00215	400AMP
AS00216	500AMP



AS00214

Fibreglass Tape



Size 2" x 3mm x 30m

AS00374

Fibreglass Cloth

Model No.	#3000
Stock Code	AS00250
Density	1600g/m ²
Temperature	550 °C
Resistance Capability	(Max Continuously)
Weave Type	Plain
Colour	White
Finish	Texturised
Thickness	3.0mm
Width	1.0m
Roll Length	15m



Fire Blanket



Stock Code	Size(m)
AN00609	4' x 6'

AN00609

Fibreglass Cloth

Model No.	HT800	#1700
Stock Code	AS00248	AS00249
Density	1650g/m ²	1100g/m ²
Temperature	550 °C	550 °C
Resistance Capability	(Max Continuously)	(Max Continuously)
Weave Type	Satin	Plain
Colour	Golden Brown	Golden Brown
Finish	Heat Treated	Texturised
Thickness	1.0mm	1.7mm
Width	1.0m	1.0m
Roll Length	50m	30m

