

ThreeBond 1700 Series

Instant Heavy Duty Adhesive

ThreeBond 1700 Series are instant heavy-duty adhesives. The adhesives adhere strongly within a few seconds on almost all substances such as metals, plastics, glass, rubber ceramics, etc., but it is not suitable for adhering materials which adsorb the adhesive such as leather, canvas, paper, wood, etc.

- For adhering weather strip rubber and door-stop rubber, firm fixing of the speed changer lever, fitting of cushion rubber and gromet and oscillation prevention of the fender mirror.
- Package...2-g and 20-g plastic containers.

Stock Code	Model	Packing
AU00041	TB1741	20g / Btl
AU00042	TB1743	20g / Btl
AU00043	TB1747	20g / Btl
AU00044	TB1781	20g / Btl
AU00045	TB1782	20g / Btl
AU00046	TB1783	20g / Btl

Stock Code	Model	Packing
AU00047	F2 Instant	20g / Btl
AU00048	TB1796BP	45g / Btl
AU00049	TB1795	50ml

AU00041



ThreeBond 1802B

Penetrative Lubricant and Corrosion Inhibitor for equipment.

Three Bond 1802B is an anti-corrosion lubricant which combines water proofing, rust proofing, lubricating and screw loosening functions into one agent that can also be used in many other applications.

- APPLICATION: Rust-prevention, lubrication and cleaning of machines, parts, tools and jigs. Loosening of seized bolts and screws.
- FEATURE: In compliance with JIS K2246-NP3
- PACKAGE: 420 ml aerosol

Stock Code	Model	Packing
AU00050	TB1802B	420ml

AU00050



ThreeBond 1804

Odorless Rust-preventive Lubricant

ThreeBond 1804 is an odorless rust-preventive lubricant. It is practically odorless, and has virtually no adverse effect on plastics. The usage applications are the same as ThreeBond 1801, but it is most suitable for the cabin of automobiles where odor is liable to become stuffy, or where plastics are assembled.

- Spray it on cabin or room which has become stuffy such as the return springs of the clutch and brakes.
- Package...20-ml aerosol-type

Stock Code	Model	Packing
AU00051	TB1804	420ml

AU00051



ThreeBond 1805

Grease-type Rust-preventive Lubricant

ThreeBond 1805 is a grease spray-type rust-preventive lubricant. When sprayed, it becomes a durable grease with soft film that can withstand high loads and closely adheres to the metallic surface. It has excellent waterproofing and weather resistance, and in particular, it withstands washing-out by rainwater and effective long-term rust prevention and lubrication. Fine for rust prevention and lubrication of outside locations which are directly exposed to sunlight and rain.

- For bonnet locks, door hinges, door locks, trunk hinges, spaces between leaf springs, spring spacers, clutch plunger squeaks, pedal squeaks, gate-door hinges, yachts, cultivators, tools, and lawn mowers.
- Package...340-ml aerosol-type

Stock Code	Model	Packing
AU00052	TB1805	340ml

AU00052



ThreeBond 1855 / 1856

Silicone Grease

This grease is made up mainly of silicone. In comparing with the petroleum oil series, the working temperature is wider. It is able to maintain its lubricity at 30-170°C. It is also stable to heat oxidation and water, making it very suitable for use on gas cooker.

- Main application: Gas cooker grease, lubricate rubber and plastic parts.
- Feature: Good stability to heat oxidation
- Packaging: 100g tube
- 1 case: 20 pieces x 5

Stock Code	Model	Packing
AU00053	TB1855	100g

Stock Code	Model	Packing
AU00054	TB1856	100ml

AU00053



ThreeBond 1901 and 1910

Molybdenum Disulfide Based Seizure Preventive Lubricants

ThreeBond 1901 and 1910 are molybdenum disulfide based seizure preventive lubricants. Molybdenum disulfide has a friction coefficient which is lower than any conventional lubricants, and is an ultra-fine-grain solid lubricant which is also extremely stable chemically and temperature wise. Through friction, it forms a lubricating film which is smooth, tough, heat resistant, pressure resistant and protects mechanical parts from wear, seizure, and gouging which are major problems of mechanical equipment.

- Use ThreeBond 1901 and 1910 to sliding parts, rotary parts, fitting-over parts and screwed parts.
- ThreeBond 1901...1-kg and 500-g canned pastes
- ThreeBond 1910...480-g aerosol-type

Stock Code	Model	Packing
AU00055	TB1901	1kg / Can
AU00056	TB1910	420ml

AU00055



ThreeBond 2082C

High Shear Strength Type

Three Bond 2082C is a two-component epoxy adhesive compound. Rubber particles are distributed within the epoxy, making the cured material non-brittle, imparting toughness and high bonding ability.

The pot life at room temperature (25 °C) is 70 minutes. About 90% of the total strength can be obtained after 24 hours.

Application

- Bonding of various metals, plastic, etc
- Repair bonding for cars, vehicle and ship
- Bonding of electrical and electronic parts
- Bonding of precision equipment
- Bonding of ski rack and other sports equipment

Stock Code	Model	Packing
AU00057	TB2082C	100g / Set

AU00057



ThreeBond 2082E

Filling Repairing Agent

Three Bond 2082E is a two-component epoxy adhesive compound. Widely use for application like filling and repairing. This production has a high adhesive strength, excellent resistance towards chemicals, water, oil and mechanical force.

Application

Bonding of various type of metals, glass, china, tile, stone, concrete, plastic, etc. (Not suitable for polyethylene, polypropylene, o-polymer)

Repairing of holes and crack of mortar, concrete, metals, etc.

Stock Code	Model	Packing
AU00058	TB2082E	1.5g / Set

AU00058

