# Chemical

#### ThreeBond 2083L Under water-hardening Type Adhesive & Filling Agent

Putty-like water-setting filler-adhesive based on epoxy resin. High bonding strength is achieved in the presence of moisture and even in water, allowing to be used in such environment where the conventional adhesive is not so effective

- Application: Bonding, filling and repairing in water and on moist faces. Bonding of hard PVC pipe, filling of cracks and holes in concrete, and bonding of tiles.
- Feature: Reacts and sets in water and under moist conditions to exert high bonding strength.
- Package: 500 g set, 2 kg set can.

#### ThreeBond 2084 For Quick, Economical Repair

Three Bond Series Repair Kits are epoxy-based compounds for repairing; cracked pipes broken tank, rejected work pieces for bonding or some metals or concrete. This series eliminates large and troublesome work to remove pipes, weld, etc. and will drastically reduce repair cost.

- Main agents (1kg) hardener (100gm), glass cloth (5 cm x 10 cm) I solvent can (200 g).
  Good adhesion on metal for bonding, filling and laminating. It S very popular in various industries such as iron and steel, electric parts, shipbuilding, petroleum, chemical, machine, vehicle, electricity, foods, VX and construction. AU00061

#### Pando 391D Gasket Remover

This is an easy-to-use, aerosol type, removing agent for gasket

- Main application: This can be used to remove gasket, packing, sealant, grease, carbon or paint. Feature: Does not attack metals
- Packaaina: 420ml aerosol
- 1 case: 10 pieces x 2

#### **Super Sealer**

Super Sealer No 1. 2. 3 are high temperature resistant silicon sealant. They are developed based on totally different concepts and leakage prevention theories from the conventional solid sheet gasket. Simply apply a layer of sealant on the flange surface of engine parts. Leakage of oil, water, gasoline can be prevented.

- Extreme high temperature resistance (-65°C to 350°C)
- Fast cure and OdourlessExcellent Oil resistance

#### **Super Lubricant**

Super Lubricant is an environment friendly lubricating agent. Developed for moisture-proofing, rust-preventive, lubrication and screw loosening agent. Its outstanding affinity for metal makes it easy to remove even deeply rusted threaded fasteners. Furthermore, the lubrication properties reduce creaking of moving parts in machinery and appliance. It is odourless and CFC free

- Agent for penetrative lubrication
- Moisture repelling
- Anti rust protective agent for metal mould

#### Super Cleaner

Super Cleaner is a fast drying cleaning agent designed for cleaning of brake in automobiles and machinery parts. Remove dirt, grease and oil effectively. It's also commonly use in Plastic Moulding companies as a industrial cleaning agent for metal mould. Most importantly, it is environmental friendly and CFC free. Stock Code

Industrial cleaner for automobile and machinery parts

- Remove grease and oil effectively
- Rapid drying nature, assist in productivity

### Super Glue

Super Glue is a heavy-duty instantaneous cyanoacrylate adhesive. The adhesive adheres strongly within a few seconds on almost all type of material. Low viscosity, easy application and usage ideal for bonding metals, glass, rubber, china wares, leather, wood & plastic materials.

• One drop permanently bonds metal, glass, rubber, wood, leather and plastic

ALLINTON ENGINEERING & TRADING PTE LTD

- Bonding can be achieved within second
- Clean, non staining or messy • Single drop hold up to 5000 lbs

SIOCK CODE	Model	Facking		
AU00074	No. 1 Grey	85gm / Tube		
AU00075	No. 2 Red	85gm / Tube		
AU00076	TB-1530C	150cc Adhesive		
AU00074				

Madal

Model


Stock Code

AU00283

AU00275 TB1803CA

Model

AU00073 PANDO391D 480g / Spray



Packing

400ml aerosol can

Packing AU00608 480ml aerosol can

AU00608

Packing

3g blister packed tube

AU00283



405



















Chemica

## **THREE BOND**

Packing

500g / Set

2kg / Set

Packing

Decking

AU00073

Stock Code

ALI00059

AU00060

Stock Code

Stack Code

Stock Code

Model

TB20831

TB2083L