




LPS 1 Greaseless Lubricant

LPS 1 displaces moisture, making it ideal for drying out electrical/ electronic components.



AU00404

Stock Code	Size
AU00404	11 oz. (312 grams)

LPS 1™ Greaseless Lubricant

- Provides a dry, thin lubricating film
- Resists oil, dust and dirt build-up
- Fast acting penetration
- Displaces moisture
- loosens rusted or frozen parts
- Provides a short term, light, corrosion resistant barrier
- Non-conductive
- Ideal for delicate mechanisms
- Used worldwide in aviation
- Safe on paint and most plastics
- Inverta Spray Valve allows one to spray in an upright or inverted position.

LPS 2 Industrial Strength Lubricant

LPS 2 is an excellent protective coating for hand and machine tools, parts and equipment.



AU00405

Stock Code	Size
AU00405	11 oz. (312 grams)

LPS 2™ Industrial-Strength Lubricant

- Strong, multi-purpose lubricant and penetrant with added corrosion protection
- Provides a nondrying, light, oily film for use on indoor/ outdoor equipment
- Reduces wear caused by friction and corrosion
- Displaces moisture
- Loosens rusted or frozen parts
- Provides up to one year of protection
- Non-conductive
- Safe on paint and most plastics
- Inverta Spray Valve allows one to spray in an upright or inverted position

LPS 3 Premier Rust Inhibitor

LPS 3 leaves a soft, self-healing, waxy film that resists moisture.



AU00406

Stock Code	Size
AU00406	11 oz. (312 grams) aerosol

LPS 3™ Heavy-Duty Rust Inhibitor

- Protects up to two years
- Stop rust and corrosion
- Provides non-sling lubrication
- Self-healing, waxy film
- Provides anti-seize coating
- Safe to use on rubber, fabric, plastics and paints

LST Penetrant

End-User Education Tip-Surface Tension is the measurement of a liquid's ability to "bead" or form droplets. The higher the surface tension, the more likely the product will bead-up on a surface and not penetrate. LST's extremely low surface tension results in instant spreading, consistent coating and deep penetration.



AU00407

Stock Code	Size
AU00407	11 oz. (312 grams)

LPS Penetrant

- Specially formulated with low surface tension for fast penetrating action
- Attacks rust and corrosion to free frozen parts
- Powerful foaming action provides complete surface coverage
- Displaces moisture
- Lubricates and protects metal surfaces
- No chlorinated solvents
- Flash point of 175 °F (79 °C)
- Inverta Spray Valve allows one to spray in an upright or inverted position.

Heavy Duty Silicone Lubricant

Heavy-Duty silicone is ideal for surfaces like rubber and plastics, where the petroleum products can not be used.



AU00408

Stock Code	Size
AU00408	13 oz. (369grams)

Heavy-duty Silicone Lubricant

- Meets FDA regulation for incidental food contact
- Meets USDA requirements for H1
- Silicone-rich formula
- Water-based formula
- Colorless & odorless
- Ideal for rubber and plastic surfaces
- Eliminates sticking, binding and squeaking
- Does not contain chlorinated solvents
- Non-straining
- Same on most surfaces

Dry Film Silicone Lubricant

Dry Film Silicone Lubricant provides excellent lubrication and is ideal for releasing molded parts.



AU00409

Stock Code	Size
AU00409	11 oz. (312 grams)

Dry Film Silicone Lubricant

- Dry film will not attract dust or dirt
- Non-flammable
- Provides excellent lubrication
- Excellent for releasing molded parts
- Excellent for high temperature applications up to 500 °F (260 °C)
- Colorless, thin film
- Does not contain chlorinated solvents
- Petroleum base