

Anti Spatter

Stock Code	Size
AU00417	13 oz. (368 grams)

AU00417



- Excellent spatter protection provides cleaner welds
- Oversized nozzle for easy use with welding gloves
- Safe, water-based formula
- Non-flammable
- Does not contain suspect carcinogens such as methylene chloride
- Does not contain silicone
- Paint compatible
- Non-toxic

Belt Dressing

Belt Dressing extends the life of drive belts by improving traction and allowing runs under reduced belt tension.

Stock Code	Size
AU00418	10 oz. (284 grams)

AU00418



- Prevents belt slippage on flat, round and V-belts
- Extends belt life
- Does not contain chlorinated solvents that deteriorate drive belts
- Fast evaporation
- Eliminates squeaks from slipping belts
- Meets USDA requirements for P1
- Colorless
- Can be used in wet outdoor conditions
- Low odor

Bearing Grease

Multi-Purpose is specifically developed to outperform conventional bearing greases and extend relubrication periods.

Stock Code	Size
AU00419	14.1 oz. (400 grams)
AU00420	5 gal. (18.93 litres)
AU00421	16 gal. (60.48 litres)

AU00419



ThermaPlex Multi-Purpose Bearing Grease

- Long life
- Excellent load carrying properties
- Extends relubrication periods
- Prolongs bearing life
- Good corrosion resistance
- Ideal for lubricating all types of bearings
- Reduces grease consumption

Appearance: Blue colored paste
Odor: Petroleum odor
Temperature Range: -22°F (-30°C) to 350°F (177°C)
Dropping Point: 429°F (220°C)
NLGI Grade: No.2
4-Ball Weld Load: >600kg
Timken "OK" Load: 50Lbs.

CFC Electro Contact Cleaner

Stock Code	Description
AU00422	CFC Free Electro Contact Cleaner
AU00499	Micro-x Fast Evaporating Contact Cleaner



AU00422



AU00499

- Fast evaporation
- No residue
- Less odor
- Non-conductive
- Does not contain HCFCs
- Safe on plastics
- Inverta Spray Valve allows one to spray in an upright or inverted position
- Packing: 11 oz (312 grams)

Contact Cleaner 140°C

Stock Code	Size
AU00423	11 oz. (312 grams)

AU00423



Electro 140° Contact Cleaner

- Flash point above 140°F (60°C)
- Superior wetting and penetrating action
- Controlled evaporation
- No residue
- Non-conductive

- Safe to use on most surfaces
- Does not contain HCFCs
- Inverta Spray Valve allows one to spray in an upright or inverted position

Citrus Base Degreaser

PreSolve tackles the toughest degreasing applications quickly. It is especially suited for removing grease, adhesives, tars and oils.

Stock Code	Size
AU00424	15 oz. (425 grams)

AU00424



PreSolve® Citrus Degreaser

- High performance citrus based degreaser
- Ideal for removing grease and oil
- Fast acting penetration
- Controlled evaporation
- Does not contain chlorinated solvents
- Non-conductive
- Safe on all metals and most plastics
- Inverta Spray Valve allows one to spray in an upright or inverted position

BrightCoat Cold Galvanize Corrosion Inhibitor

Brightcoat Cold Galvanize provides a shiny zinc coating to prevent rust and corrosion.

Stock Code	Size
AU00425	13 oz. (368 grams)

AU00425



- Shiny zinc coating
- Prevents rust and corrosion on all metals
- Restores hot dip galvanizing
- Dries to touch in 15 to 30 minutes
- Repairs rusted, galvanized and welded surfaces
- Electrochemically protects bare metal

- Heat resistant, flexible coating
- Will not yellow, chalk, crack or peel
- Meets performance requirements of ASTM A780-93A

Cold Galvanize Corrosion Inhibitor

Cold Galvanize works as a paint primer over rust.

Stock Code	Size
AU00426	14 oz. (397 grams)
AU00427	1gal. (3.78 litres)

AU00426



- 95% zinc-rich galvanized coating
- Works like a hot-dip on ferrous metals indoors and outdoors
- Withstand water temperature up to 212°F (100°C) and continuous dry heat up to 750°F (400°C)
- Commonly used as a flash rust preventive on welded areas
- Long term protection
- Flexible coating will not yellow, chalk, crack or peel
- Electrochemically protects bare metal
- Dries in 3-5 minutes.