

## Cutting Fluids –Tapmatic #1 Gold

Stock Code	Size
AU00524	11 oz. (312 g) aerosol
AU00525	16 fl. oz. (0.473 litres)
AU00526	1 gal. (3.78 litres)
AU00527	5 gal. (18.93 litres)
AU00528	55 gal. (208 litres)

AU00524



- Great for steel and aluminium
- Excellent for low speed, high pressure applications
- Minimizes torque increases
- Does not contain chlorinated paraffins, water solvents or inactive fillers
- Aerosol provides a pinpoint stream with foaming action
- Safe on all metals

## Cutting Fluids –Tapmatic Dual Action Plus #1

Stock Code	Size
AU00518	16 oz. liq (0.473 litres)
AU00519	1 gal. (3.78 litres)

AU00518



- Made for hard to machine alloys such as stainless steel and titanium
- Reduces friction and eliminates chip welding
- Lowers temperature through chemically controlled evaporation
- Provides ultrafine finishes and precise tolerances

## Cutting Fluids – Tapmatic Dual Action Plus #2

Stock Code	Size
AU00520	16 oz. liq (0.473 litres)
AU00521	1 gal. (3.78 litres)



AU00520

- Provides superior extreme pressure lubricity in machining aluminium and its alloy.
- Reduces friction and eliminates chip welding.
- Improves surface finish and extends tool life.

## TKX All-Purpose Penetrant, Lubricant and Protectant

Stock Code	Size
AU00462	11 oz. (312 grams)
AU00463	1 gal. (3.78 litres)

AU00462



- Excellent all purpose lubricant
- Displaces moisture
- Loosens rusted or frozen parts
- Protects against corrosion
- High flash point of 175°F (79°C)
- Does not contain chlorinated solvents or silicones
- Non-conductive
- Safe on fabric, plastic, paint and other finishes
- Inverta Spray Valve allows one to spray in an upright or inverted position

## ThermaPlex Aqua Bearing Grease

Aqua is formulated to withstand the effects of running water and to provide long lasting lubrication even when fully submerged in fresh or salt water.

Stock Code	Size
AU00553	5 gal. (18.93 litres)
AU00554	14.1 oz. (400g)
AU00555	16 gal. (60.48 litres)



AU00553

- Excellent resistance to fresh and salt water
- Resists water washout
- Good adhesion properties
- Excellent corrosion resistance
- Significant load carrying capability
- Reduces wear
- Reduces grease consumption
- Greater degree of bearing protection

## Red & Redi Multi-Purpose Red Grease

Red & Redi's exceptional adhesive and cohesive properties resists throw-off at high speeds. A specially formulated additive package in Red & Redi provides it with extreme pressure and anti-wear properties.

Stock Code	Size
AU00513	11 oz. (312 grams)

AU00513



- Delivers excellent lubrication
- Prevents rust, corrosion and oxidation
- Red color allows easy visual inspection
- Remains effective at extremely high temperatures 550°F (288°C)
- Penetrates quickly
- Reduces friction and vibration
- Resists shock

## Hand Cleaner Towels

Workplace Hand Cleaner Towels reduce downtime with convenient, waterless hand cleaning at the workstation.

Stock Code	Size
AU00517	Bucket of 72 Towels

AU00517



- Fast acting
- Disposable
- Portable
- Premoistened
- Residue free
- Non-scratching abrasive
- Pleasant fragrance
- Boiling Point: 212°F (100°C)
- Vapor Density: Greater Than One
- Specific Gravity: 97
- VOC: 110g/L
- pH: 7.5 ± 0.5
- Appearance and Odor: Opaque white liquid with a fresh citrus scent saturated onto towels
- Flash Point: None to boiling (TCC)

## Strong Steel Stick Renewal Composite

Stock Code	Size
AU00539	4 oz. (114 g)



AU00539

- Hand-kneadable, ready-to-use stick for fast emergency repairs
- Hardens like steel in 20 minutes
- Can be machined, drilled, tapped and painted in 30 minutes
- Plugs and seals leaks
- Permanently fill gaps and holes in metal, concrete, wood, fiberglass and ceramics
- Patches holes and cracks in pipes, drums and tanks
- Can be used for underwater repairs

ALLINTON ENGINEERING & TRADING PTE LTD

331 Jalan Besar Singapore 208983

T65 6296 0679 W allinton.com.sg E sales@allinton.com.sg