

Rotary Cutter



AH04093



AH04099

Stock Code	Model No.	Pipe Capacity			Length		Weight	
		Steel (inch-nom.)	Cast Iron & Ductile (inch-nom.)	Actual (O.D.mm)	in.	mm	lb.	kg
AH04093	LCRC8S	6-8		159-246	58	1473	42.6	19.4
AH04094	LCRC8I		6-8	159-246	58	1473	42.6	19.4
AH04095	LCRC12S	10-14		266-358	61	1549	50	22.7
AH04096	LCRC12I		10-12	266-358	61	1549	50	22.7
AH04097	LCRC16S	16-18		368-462	66	1664	60	27.3
AH04098	LCRC16I		14-16	368-462	66	1664	60	27.3
AH04099	RC20S	20-22		476-572	106	2680	89	40.5
AH04100	RC20I		18-20	476-572	106	2680	89	40.5
AH04101	RC24S	24-26		584-660	111	2807	107	48.6
AH04102	RC24I		22-24	584-660	111	2807	107	48.6
AH04103	RC30S	28-34		698-864	96	2438	283	128.6
AH04104	RC30I		30	698-864	96	2438	283	128.6
AH04105	RC36S	32-36		813-915	96	2438	295	134.1

Rotary Cutter Wheel



AH04107



AH04123

Stock Code	Model No.	Blade Exposure	Standard Pack	Fits (Reed Cutter)	Application
AH04107	RCS8-36	16.1mm (0.635in)	4	LCRC8; LCRC12; LCRC16; RC20; RC24; RC30; RC36; RC42	Steel; Stainless Steel
AH04123	RCI8-30	12.7mm (0.500in)	4	LCRC8; LCRC12; LCRC16; RC20; RC24; RC30; RC36	Cast Iron; Ductile Iron (manual)
AH04124	RCX	20.3mm (0.800in)	4	LCRC8; LCRC12; LCRC16; RC20; RC24; RC30; RC36; RC42	Heavy Wall Steel; Stainless Steel

Hinged Cutter Blade



AH04137

Stock Code	Model No.	Blade Exposure	Standard Pack	Fits	Application
AH04137	HS4 #03504	8.1mm (0.320in)	4	Reed (3-1; 3-3; 3-4; H4; LCRC4) Wheeler Rex 95041	Steel; Stainless Steel
AH04120	HS6 #03506	9.9mm (0.390in)	4	Reed H6; Wheeler Rex 95061	Steel; Stainless Steel; Copper
AH04121	HS8-12 #03508	11.4mm (0.450in)	4	Reed (H8; H12) Wheeler Rex 95081; 95121	Steel; Stainless Steel
AH04122	HX6 #03514	12.1mm (0.476in)	4	Reed H6	Steel; Stainless Steel

Outboard Roller



AH04141

- Outboard roller is for use with all cutter wheels except the RCX wheel.
- Each cutter wheel requires two outboard rollers for a total of eight per cutter.
- Model No. RC8-30OR