

## Magnetic Drill Set

### UNI 5000 Xtreme 2-Speed



AC 01026  
AC 01027

Cutter 50mm  
Cutting Shank 19mm  
Twist Drill Capacity 13mm  
Clamping Force 1,000kg  
Size 610mm x 280mm x 460mm  
Weight 14kg

Motor					
Stock Code	Volts	Cycles	Amps	Power	No Load Speed
AC01026	120V	50/60Hz	10A	1100W	650/450r.p.m
AC01027	220V	50/60Hz	5A	1100W	650/450r.p.m

Standard Accessories  
1 Oil Tank, 1 Guard, 1 Safety Chain, Crank Handles,  
1 Hex. Wrench: 2.5mm,  
1 Hex. Wrench: 6mm, 1 Auxiliary Handles

### UNI 7500



Optional no. 3 morse taper accessories available for tapping up to 25mm, taper 3 shank twist drills up to 32mm, chucks, reamers, countersinks and more.



Bit not included

AC 01029  
AC 01030


Cutter 75mm  
Cutting Shank 19mm  
Twist Drill Capacity 32mm  
Taps 25mm  
Morse Taper No.3  
Clamping Force 2,250kg  
Size 630mm x 280mm x 470mm  
Weight 27.7kg

Motor					
Stock Code	Volts	Cycles	Amps	Power	No Load Speed
AC01029	120V	50/60Hz	15A	2200W	450/280r.p.m
AC01030	220V	50/60Hz	7.5A	2200W	450/280r.p.m

Standard Accessories  
1 Hex. Wrench: 2.5mm, 1 Wrench 8mm, 3 Crank Handles,  
1 Guard, 1 Safety Chain



### UNI 3000 Auto



AC 01035  
AC 01036

Cutter 35mm  
Cutting Shank 19mm  
Twist Drill Capacity 13mm  
Clamping Force 800kg  
Size 570mm x 240mm x 520mm  
Weight 17kg

Motor					
Stock Code	Volts	Cycles	Amps	Power	No Load Speed
AC01035	115V	60Hz	10A	1100W	620r.p.m
AC01036	230V	60Hz	5A	1100W	620r.p.m

Standard Accessories  
1 Hex. Wrench: 4mm & 2.5mm, 3 Crank Handles, Safety Chain, Side Handles, 1 Oil Tank, 1 Guard

### UNI 3500



AC 01038  
AC 01039

Cutter 35mm  
Cutting Shank 19mm  
Twist Drill Capacity 13mm  
Clamping Force 800kg  
Size 520mm x 170mm x 470mm  
Weight 14.8kg

Motor					
Stock Code	Volts	Cycles	Amps	Power	No Load Speed
AC01038	120V	50/60Hz	10A	1100W	550r.p.m
AC01039	220V	50/60Hz	5A	1100W	550r.p.m

Standard Accessories  
1 Guard, 1 Hex. Wrench: 6mm, 3 Crank Handles, 1 Auxiliary Handles, 1 Hex. Wrench: 2.5mm, 1 Oil Tank, 1 Safety Chain

### Low Profile Magnetic Drill



AC01225

#### Specifications

Stock Code	AC 01224	AC 01225
Model No	UNI 3530	
Power input	1100W	
Voltage	110V / 50-60Hz	220V / 50-60Hz
No Load / Full Load RPM	450/390	
Max Capacity Dia x Depth of cut	35mm x 30mm	
Weldon shank	19mm	
Magnetic Adhesion	15000 N	
Overload Protection	With	
Dimension	285x101x200mm	
Net Weight	10kg (22.4lbs)	

UNICUT