

SMAW/ MMA WELDING MACHINE

ARC200DC



Features:

- Dual voltage 115/230V
- Cellulosic electrode E6011 capability
- Professional quality IGBT Inverter
- Anti-stick, arc force, Lift TIG
- Single PCB, compact size, lightweight
- Easy arc starting, minimal spatter
- Auto-compensation for voltage fluctuation



Stock Code	AS00820	
Model No.	ARC 200 DC	
Input power source	1~AC110V±15% 50/60HZ	1~AC220V±15% 50/60HZ
Rated input current (A)	54.7	42.7
Rated input power capacity (KVA)	6	9.7
Output current range (A)	20-140	20-200
No-load voltage (V)	85	
Rated duty cycle (%) @40°C	25	
Efficiency (%)	85	
Power factor (cosφ)	0.7	
Protection class	IP21S	
Insulation class	F	
Dimensions (mm)	381 x 138 x 286	
Weight (Kg)	6.8	

Package Includes:

Stock Code	Description
AS00820	Veloce Arc 200DC (Dual Voltage) 110V/220V
AS00900	Electrode Holder WSA-300A
AS00901	Earth Clamp 300A
AS00116	300A Neoprene Welding Cable (25mm ² x 3m)
AS00941	Female Receptacle 50-70mm ²
AS00903	DKJ35-50 Connector (Male)

Optional Accessories:

Stock Code	Description
AS00900	Electrode Holder WSA-300A
AS00901	Earth Clamp 300A
AS00116	300A Neoprene Welding Cable (25mm ² x 3m)
AS00941	Female Receptacle 50-70mm ²
AS00903	DKJ35-50 Connector (Male)